

Instruments and Mounting Kits



Removable Cover

3 line LCD Display

- Two 12-digit Alphanumeric lines
- Both Flow Rate and Total Flow appear together
- Third line shows Output Status Icons
- Backlit Display is available for F9.00, F9.02, F9.03, F9.50, F9.51



Up to 3 LEDs

- For output status indication

5 Button Silicone Rubber Keypad

1/4 DIN size Monolithic Enclosure

The same instrument may be mounted three different ways using mounting kits



Direct Mounting to Flow Sensor

Panel Mounting

Wall Mounting



Direct Mounting Kit



Panel Mounting Kit



Wall Mounting Kit



F3.01 Flow Sensor (Hall or Coil Effect)



Panel Mount Flow Instrument



Wall Mount Flow Instrument



Direct Mounted Flow Instrument

Direct Mount package consists of a flow instrument, flow sensor and direct mounting kit.

The **K9.KC1** kit includes an ABS enclosure with EPDM gasket for NEMA 4, 4X watertight installation, a cap and locking ring for connecting the sensor to the enclosure, plus four screws to attach the instrument.

Panel Mount instrument consists of a flow instrument and the panel mounting kit.

The **K9.KP1** kit includes a metal mounting clip and a neoprene gasket for NEMA 4, 4X watertight installation. The monitor fits a standard 1/4 DIN (96 mm x 96 mm or 3.78" x 3.78") panel cutout.

Wall Mount instrument consists of a flow instrument and the wall mounting kit.

The **F9.KW1** kit includes an ABS plastic NEMA 4, 4X surface mount enclosure, EPDM gasket for NEMA 4, 4X watertight installation, plus screws for attaching the instrument.

The **F9.KW2** includes in addition a 110/230 VAC to 24 VDC power supply mounted inside the ABS enclosure to provide a regulated low voltage to the flow monitor.